



ESS Solution

FES-16K-LVB

FES-16K-LVB



Comprehensive Protection

Advanced BMS with active fuse



Superior Performance

Support Max. 1C charge & 1.2C discharge GaN MOSFETS: 50% loss reduction, high-temp resistance



Optimized Energy Density

Integrated PACK: reduced line loss, enhanced energy density



Flexible Expansion

Max. 32 units in parallel



Easy Maintenance

Auto-networking, Local monitoring mode for battery, remote monitoring mode for ESS



Reliable Durability

Operates reliably in -20 °C to 55 C, natural cooling



+91 89258 27701



sales@festonsev.com

ESS Solution



Model FES-16K-LVB

Main Parameters		
Battery Chemistry		LiFePO ₄
Capacity		314 Ah
Scalability		Max. 32 pcs in parallel
Nominal Voltage		51.2 V
Operating Voltage		44.8 V ~ 57.6 V
Nominal Energy		16 kWh
Charge Current ^[1]	Max. Continuous	160 A
	Peak	280 A (10 sec)
Discharge Current ^[1]	Max. Continuous	230 A
	Peak	280 A (10 sec)
Other Parameter		
Recommend Depth of Discharge		90% DoD
Dimension (W × H × D) (Without hanging board)		400 × 708 × 233 mm
Weight Approximate		109 kg
LED Indicator		LED (SOC, working, protecting) & Buzzer
IP Rating of Enclosure		IP21
Operating Temperature		Charge: 0~55°C/ Discharge: -20°C~55°C
Storage Temperature		0~35°C
Relative Humidity		95% (non-condensing)
Altitude		≤3000m
Cycle Life		≥6000(25°C±2°C,70%EOL)
Installation		Wall-Mounted, Floor-Mounted, Stack-Mounted
Communication		CAN2.0, RS485, Bluetooth+APP
Warranty Period ^[2]		10 years
Energy Throughput ^[2]		50 MWh
Certification		UN38.3, CE, CB

[1] The current is affected by temperature and SOC.

[2] Conditions apply, refer to FesTen Warranty Letter.